

# Z6 SERIES

# 7.0 KVA

6G EUROPEAN - PV 8500  
ON GRID WITH ENERGY STORAGE HYBRID



# 8500W DUAL MPPT



## KEY SALIENT FEATURES

- ✓ Introducing 1st Time In Pakistan Real 6th Gen European Inverter.
- ✓ Single Phase Inverter, Supports three phase when installed in Parallel
- ✓ 100% Pure Sine Wave Solar Inverter
- ✓ Built-in Wi-Fi (10 meter range) & available for Android devices
- ✓ Inverter running with battery & without battery
- ✓ Built-in Battery equalizations/BMS (Battery Management System)
- ✓ Multiple operation modes (On Grid / Of Grid/Hybrid)
- ✓ Grid-Tied net metering feature with 100% reverse grid feeding
- ✓ Adaptable to main Voltage/generator power
- ✓ Conformal coating to prevent from dust and humidity
- ✓ New Smart Color Screen LCD with touch buttons
- ✓ Built-in anti dust for harsh environment
- ✓ Compatible with all kinds of Lithium Batteries (Multiple Parameters)
- ✓ Surge Capacity 2\* Rated Power for 5 Seconds
- ✓ Energy generated record, load record, history information fault record
- ✓ Parallel upto 9 Units
- ✓ Built-in Dual MPPT parallel based 8500W solar charge controller (160A)
- ✓ Smart power management set multiple schedules
- ✓ Communication ports RS232/USB/RS485/CAN
- ✓ Zero transfer time
- ✓ 98% Real time sharing
- ✓ Overload Protection on 150% Load

Multiple  
RGB Lights

Z6  
SERIES

PV  
8500

- ✓ High PV input voltage range (120~500 VDC)
- ✓ Dual AC Output
- ✓ Maximum PV input current 36A
- ✓ Built-in Zero export
- ✓ European Design and Engineered in Taiwan



BUILT-IN  
WI-FI



BATTERY  
OPTIONAL



ON-OFF  
GRID



PARALLEL UP  
TO 9 UNITS



REVERSE  
GRID FEEDING



SMART LOAD  
MANAGEMENT



TOUCH BUTTON  
SCREEN

1st TIME IN PAKISTAN  
6th GENERATION SOLAR HYBRID  
INVERTER WITH EUROPEAN DESIGN


MODEL	Z6 - 6G EUROPEAN PV8500   7 KVA
Rated Power	7000VA/ 6500W
<b>INPUT</b>	
Voltage	230VAC
Selectable Voltage Range	90-280VAC (For Home Appliances) / 170-280VAC (For Computer)
Frequency Range	50Hz/60Hz (Auto Sensing)
<b>OUTPUT (OFF GRID OPERATION)</b>	
AC Voltage Regulation (Batt.Mode)	230VAC±10%
Overload (Line mode)	5a @>150% load; 10s @110%-150% load; 100ms @>200% Load
Efficiency(Peak)	98%
Transfer Time	10ms (For Personal Computers); 20ms (For Home Appliances)
Wave form	Pure Sine Wave
<b>OUTPUT (GRID-TIE OPERATION)</b>	
Nominal Output Voltage	220/230/240 VAC
Output Voltage Range	184-264.5 VAC or 195.5 - 253 VAC (Selectable)
Nominal Output Current	29.54A
<b>BATTERY</b>	
Battery Voltage	48VDC
Floating Charge Voltage	54VDC
Overcharge Protection	63VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>	
Solar Charger Type	DUAL MPPT (PARALLEL)
Maximum PV Array Open Circuit Voltage	500VDC
Maximum PV Array Power	8500W 98%
MPPT Range @ Operating Voltage	120~450 VDC
Maximum Solar Charge Current	80A + 80A = 160A
Maximum PV Input Current	36A
Nominal PV Voltage	240 VDC
Maximum AC Charge Current	60A
<b>PHYSICAL</b>	
Dimension.D*W*H(mm)	224 x535 x 425 mm
Net Weight (kgs)	13.5 KG
Communication Interface	USB and Rs232
<b>OPERATING ENVIRONMENT</b>	
Humidity	0 to 90% Relative Humidity (Non-condensing)
Operating Temperature	-10 C to 50 C
Storage Temperature	-15 C to 60 C

Note: Product specifications are subject to change without further notice



Built-in Wifi  
Monitoring

Touchable  
Buttons



Wi-Fi App



WI-FI DEVICE  
OPTIONAL